



LOCKING POSITION



COUPLING POSITION

SIZE OF SOCKET SUITABLE
FOR BALL 16 mm WITH
SUFFICIENT CLEARANCE

LOCKING POSITION & COUPLING POSITION OF 'W'. CLIP

- H.D.G. HOT DIP GALVANISED E.G. ELECTRO GLVANISED

12	W. PIN .79 x 1.5	PHOSPHER BRONZE	1
11	WASHER SPRING 2mm Thk.	SPRING STEEL E.G	2
10	WASHER PLAIN 2mm Thk.	MILD STEEL/EG	2
9	'U' BOLT & NUTS (ø12x70mm)	MILD STEEL/H.D.G.	2
8	KEPPER PIECE	ALUMINIUM ALLOY	1
7	STRAIN CLAMP BODY	ALUMINIUM ALLOY	1
6	BALL EYE 3ø x ø10 ±1mm.	FORGED STEEL	1
5	RIVET ø16 x 65	MILD STEEL H.D.G	1
4	STRAPS 35 x 6	MILD STEEL H.D.G	2
3	SPLIT PIN ø4 x 38mm ±1	BRASS	2
2	WASHER PLAIN 3mm Thk. FOR ø16	MILD STEEL H.D.G.	2
1	BOLT HEX WITH NUT M16x145	MILD STEEL H.D.G.	1
NOS SR.	DESCRIPTION	MATERIAL	QTY.

**MADHYA GUJARAT VIJ COMPANY LTD.,
SARDAR PATEL VIDYUT BHAVAN,
CORPORATE OFFICE, RACE COURSE,
BARODA - 390 007**

DRG. TITLE :	SOCKET ENDED STRAIN CLAMP (SNAIL TYPE) FOR DOG CONDUCTOR.
--------------	--

DRG. NO. :	01-DOG HW
------------	-----------